

HT-SERIES NEW ADDITIONS



THE HIGH PERFORMING HT-SERIES for commercial settings, once exclusive to the aerospace industry, can safely put out fires without damaging electronic equipment, specialized machinery, or other delicate materials. That also means that there is no clean-up or down time for your operations. Industries such as healthcare, clean manufacturing, data processing centers, and museums benefit from the HT Series. These extinguishers are also sensitive to the environment, meeting strict environmental regulations for Global Warming Potential and Ozone Depletion Potential. With knock-down power and firefighting efficiency, the HT-Series using Halotron BrX agent features aluminum cylinders (Model 551 uses a steel cylinder), durable high-gloss polyester powder paint, and all-metal valve construction. Maximum visibility during discharge, a large stainless steel pull pin, and no electronic conductivity back to the user make these extinguishers extremely easy to use.



551
P/N 28084



549
P/N 28204



547
P/N 28202



A537TS
P/N 28207

RUGGED

- 6-Year manufacturer's warranty
- 12-year service life; non-rechargeable
- Stored-pressure design for simple inspection
- Durable, high-gloss polyester powder-coat finish
- All-metal valve construction
- Robust cylinders crafted from high-quality steel or aluminum
- 7-day atmospheric lifespan
- A low-GWP and very low-ODP product
- Temperature range -40°F to 120°F

USER-FRIENDLY

- Leaves no residue
- No thermal or static shock
- Flexible hose, all-metal hose for easy use
- QR coded and multilingual labels



MODEL 551 SHIPS WITH A WALL BRACKET.

MODEL 809 VEHICLE BRACKET IS SOLD SEPARATELY.

MANUFACTURED AND TESTED TO UL STANDARDS
COMPLIES WITH NFPA 10 STANDARD
ISO-9001 AND ISO-14001 CERTIFIED
UL LISTED

CONFORMS TO TEST STANDARDS:
CAN/ULC-S508 - UL 2129 &
CAN/ULC-S566 - UL 711

AGENT TYPE	HALOTRON® BrX (2-BTP)			
VALVE TYPE	Anodized Aluminum			
DESIGN	Nozzle		Hose & Nozzle	
MODEL NUMBER	A537TS	547	549	551
UL & ULC RATING	2B:C	5B:C	5B:C	2A:10B:C
CAPACITY (LBS.) / (KG)	1.79 / 0.81	3.75 / 1.7	3.75 / 1.7	12.5 / 5.67
*SHIPPING WT. (LBS.) / (KG)	3.87 / 1.76	4.79 / 2.17	5.04 / 2.29	19.88 / 9.02
HEIGHT (IN.) / (MM)	11.25 / 285.75	17.59 / 446.9	17.59 / 446.9	20.25 / 514.3
WIDTH (IN.) / (MM)	4 / 101.6	4 / 101.6	5.88 / 149.35	8.5 / 215.9
DEPTH (IN.) / (MM)	3.25 / 82.6	3.25 / 82.6	3.25 / 82.6	5 / 127
RANGE (INITIAL- FT. / M)	7-8 / 2.13-2.44	10-12 / 3.05-3.66	10-12 / 3.05-3.66	15-17 / 4.57-5.18
DISCHARGE TIME (SEC.)	9	9	9	16
MINIMUM CONFINED SPACE REQUIREMENTS (FT³ / M³)	427 / 12.09	896 / 25.37	896 / 25.37	2,988 / 84.6
NOMINAL OPERATING PRESSURE	90 PSIG	100 PSIG	100 PSIG	150 PSIG
INCLUDED BRACKET	Vehicle	Wall	Wall	Wall

*Shipping weight includes box.

7595 Gadsden Hwy.
P.O. Box 81
Trussville, AL 35173

Ph (205) 655-3271
customer.service@amerex-fire.com
intl.sales@amerex-fire.com

www.amerex-fire.com
webstore.amerex-fire.com

Quality is Behind the Diamond®