



SF 1230™ WHEELED EXTINGUISHERS

STANDARD FLUIDS™ SF 1230™ FIRE PROTECTION FLUID

This extinguishing agent has a Global Warming Potential of 1 and an atmospheric life of just five days making it the long-term sustainable choice that also has the greatest margin of safety of any of the clean agents in the marketplace today.

FEATURES

- Environmentally friendly SF 1230™ Clean Agent (0 ODP - 1 GWP)
- Chrome-plated brass operating valve
- Heavy-duty steel cylinder, carriage, and hose hanger assembly
- DOT/TC Cylinders
- Lunette ring for pintle hook towing
- Pressure gauge protected by a stainless-steel gauge guard
- UL/ULC label with QR code
- Large instruction pictogram
- Operating temperature range: -40° to +120° F.
- 6-Year Warranty

SPECIFICATIONS	SF 1230™
MODEL NUMBER	775
AGENT TYPE	SF 1230
UL & ULC RATING	3A:80B:C
CAPACITY (LBS. / KG)	150
SHIPPING WT. (LBS. / KG)	395
HEIGHT (IN.)	61
WIDTH (IN.)	29
DEPTH (IN.)	42
DISCHARGE TIME (SEC.)	22
CYLINDER	DOT 4BW240
DISCHARGE RANGE (FT.)	30
HOSE LENGTH (FT.)	40
HOSE DIAMETER (IN.)	1.0
WHEELS [SEMI-PNEU] (IN.)	16 X 4
USCG APPROVED	YES



775

CONFORMS TO TEST STANDARDS:
CAN/ULC-S566 - UL 2129 & CAN/ULC-S508 - UL 711

Quality is Behind the Diamond®

7595 Gadsden Hwy.
P.O. Box 81
Trussville, AL 35173

Ph (205) 655-3271
customer.service@amerex-fire.com
intl.sales@amerex-fire.com

www.amerex-fire.com
webstore.amerex-fire.com